



**M-6880-B50**  
**OIL FILTER ADAPTOR**  
**BILLET 90 DEGREE OIL FILTER ADAPTOR FOR PUSHROD V8 ENGINES**

NO PART OF THIS DOCUMENT MAY BE REPRODUCED WITHOUT PRIOR AGREEMENT AND WRITTEN PERMISSION OF FORD PERFORMANCE PARTS © Ford Motor Company 2020

**PRIOR TO INSTALLATION READ THESE INSTRUCTION COMPETELY**  
**For questions, Call the FORD PERFORMANCE Techline 1-800-367-3788**

Please visit <https://www.performanceparts.ford.com> for warranty information



**OVERVIEW:**

**Fits 289/302/351W/351C/351M/400/429/460 engines.**

This sheet contains important information regarding the M-6880-B50 Oil Filter Adapter. This adapter allows the oil filter to be rotated to provide greater access and fitment flexibility. This adapter is designed to use a M-6731-FL820, Motorcraft FL820S or Motorcraft FL500S.

**KIT CONTENTS:**

The following parts are included:

- (1) oil filter adaptor (blue anodized)
- (1) adapter fastener (black anodized)
- (1) Parker 2-125-N674-70 (Buna 70)
- (1) Parker 64x3-N674-70 metric (Buna 70)

**FEATURES AND SPECIFICATIONS:**

Part Number	M-6880-B50
Material Adapter	6061 Aluminum (blue anodized)
Material Adapter Bolt	7075 or 2024 Aluminum (black anodized)
Adapter Bolt Torque	25 lb * ft

**OIL FILTER Part Number**

**M-6731-FL820, Motorcraft FL820S or Motorcraft FL500S:**

- Step 1.** Verify that the mating surface on the block is clean and free of imperfections.
- Step 2.** Lightly oil adapter to block O-ring and adapter bolt O-ring.
- Step 3.** Lightly oil internal threads on adapter bolt.
- Step 4.** Loosely install adapter, loosely install oil filter.
- Step 5.** Rotate to best position for your application, torque bolt to 25 LB FT
- Step 6.** Remove filter and lubricate seal. Install filter following manufacturers recommendation for tightening.

Ford Factory Shop Manual purchase options [www.motorcraftservice.com](http://www.motorcraftservice.com)