



M-6200-A75 Connecting Rods INSTALLATION INSTRUCTIONS

NO PART OF THIS DOCUMENT MAY BE REPRODUCED WITHOUT PRIOR AGREEMENT AND WRITTEN PERMISSION OF FORD RACING PERFORMANCE PARTS.

Please visit www.fordracingparts.com for the most current instruction information

**!!! PLEASE READ ALL OF THE FOLLOWING INSTRUCTIONS CAREFULLY PRIOR TO INSTALLATION.
AT ANY TIME YOU DO NOT UNDERSTAND THE INSTRUCTIONS, PLEASE CALL THE FORD RACING
TECHLINE AT 1-800-367-3788 !!!**

INSTALLATION INSTRUCTIONS:

The M-6200-A75 connecting rods are unmodified Marine/Truck production rods. Center-to-center length is 6.605" nominal. The engine builder must weight balance the rods by machining the weight pads on each end. Recommended weight match is +/- 1.5 grams at each end.

The rods are designed to use the Ford 1.040" nominal diameter piston pin (or equivalent) with a press fit. Pistons should be assembled to the rods by a qualified engine shop.

Torque rod bolts to 45-50 ft./lbs. using 30-weight engine oil.

Factory Ford shop manuals are available from Helm Publications, 1-800-782-4356